

Technical Data Sheet

NXT COOL COAT



Coverage Rate:
160 ft²/ Gal per Coat

Roller Recommendation:

Main Feature:
Advanced self-cleaning nanotechnology
100% waterproof
Excellent resistance to surface spoilage bacteria, moss and lichen



Packaging:
5 Gal



Sheen Levels:
High gloss or low sheen



Colors:
Opaque white
Colored viscous liquid

Product Description:

NXT Cool Coat is an innovative, nanotechnology modified acrylic polymer coating designed to substantially lower surface friction to significantly reduce dirt retention and ultimately, aide in the self-cleaning ability of the coating.

NXT Cool Coat utilizes the latest exterior grade ultra-high durability fade resistant and infra-red reflective pigments which are also highly resistant to chemicals. The performance benefits of these high-performance pigments provide a 70°F - 90°F reduction in roof surface temperature, translating to 43°F - 50°F cooler inside the building.

NXT Cool Coat offers outstanding long-term exterior durability which will stay cleaner and retain color and gloss longer than any conventional acrylic roof coating on the market.

Features:

- Available in high gloss or low sheen finishes
- 46 standard shades and can be custom color matched upon request
- Infra-red heat reflective pigments with outstanding exterior durability
- Advanced self-cleaning nanotechnology
- 100% waterproof
- Water based & Low VOC
- Excellent resistance to surface spoilage bacteria, moss and lichen

Safety Precautions:

Observe all Occupation Health and Safety (OH&S) precautions.
Refer to the relevant Safety Data Sheets (SDS) for product safety related information.

For further information and support:

Nutech Paint +61 3 9770 3000

<https://nutechpaint.com.au/>

KEEP AWAY FROM HEAT, OPEN FLAMES AND ALL SOURCES OF IGNITION

- Always keep the container tightly closed when not in use
- Vapor is heavier than air
- Use only with adequate ventilation and avoid inhaling vapor
- Avoid contact with eyes, skin and clothing
- Wash thoroughly with soap and water after handling

- DO NOT ingest
- Use impervious gloves and appropriate eye protection

For extended use or in areas with poor ventilation, use approved respiratory protection in accordance with applicable federal, state, and local regulations.

Product Attributes:

Chemical Type: Water based exterior durable acrylic polymer

Appearance: Opaque white or colored viscous liquid

pH: 8.5 - 9.0

VOC (Coating): <50 g / 0.26 Gal

Infrared Reflectance: 30-91

Total Solar Reflectance (US EPA Energy Star Threshold – steep slopes >10°) : >25% - 91%*

Thermal Emittance: 88-94

Solubility: Soluble in Water

Minimum Film Forming Temperature: 50°F

*Subject to color selection

Suitable Substrates:

Suitably primed surfaces, including Concrete & Terracotta Roof tiles, Sheet Metal, Asbestos & Cement Sheet, Timber & Wood and Asphalt Shingles & Sheet

Substrate Note:

Treating moss and lichen prior to cleaning will minimize cleaning time.

Nutech Hypo and **Nu-EcoSafe MossRid** are recommended.

All bare surfaces must be cleaned and primed.

High pressure clean using a minimum of 3000psi.

Improperly prepared surfaces may result in coating failure.

Note:

DRINKING WATER COLLECTION

Always disconnect water tanks before cleaning and coating. Thoroughly flush gutters and allow several good rains to remove all overspray before reconnecting tanks.

Application Procedure:

NOTE: Tile pointing must be adequately cured in cold weather prior to coating to ensure adhesion.

Weather conditions must be favorable as rain, moisture or dew may cause damage to the coating.

Application in extreme hot or cold temperatures will affect gloss and durability.

Nutech Paint recommend **NXT Cool Coat** is applied by Trained Professionals.

(Where applicable) Any damaged pointing should be repaired with **Nutech MaxiPoint** as outlined in the MaxiPoint TDS.

Primer Application: Refer to the relevant Nutech Paints product TDS or contact your Nutech Paint representative for the best product for your project.

Top Coat: Observe recommended spread rate and film thickness' as noted in this TDS

- **1st:** Apply 1 even coat of **NXT Cool Coat** allowing a minimum 4 hours prior to recoat.
- **2nd:** Apply 1 even coat

Test Patch:

When recoating an existing coating, conduct a test patch to check intercoat adhesion.

If the existing coating is peeling or flaking refer to the Nutech Roof Coating Manual; Existing Painted Surfaces.

Provisions:

Application Conditions:

- Only apply in ambient air temperatures between 50°F and 86°F
- Ensure no surface moisture is present prior to application
- Consideration must be given to other climatic conditions such as wind and relative humidity

DO NOT overcoat primers or undercoats until the undercoat is completely dry. Coating in very hot conditions may reduce gloss appearance and durability.

Failure to observe these provisions may affect coating adhesion.

Application:

- Airless Spray (Recommended)
- Brush
- Roller

Mixing / Thinning:

Prior to Commencement: Stir thoroughly prior to use.

Thinning Not required or recommended.

Coverage/Spread Rate & Coats:

160 ft² / Gal per coat.

Wet Film Thickness (two coats) 20 mils.

Dry Film Thickness (two coats) 8 mils.

To maximise performance do not over spread.

Recoat: 4 hours minimum.

Drying times will vary depending on ambient temperatures or high humidity.

Application Equipment:



Air Spray



Brush



Roller

Drying Times:

Dry Film 24 hours

Weatherproof (Vertical) 24 hours

Weatherproof (Horizontal) 72 hours

Packaging/Available Sizes:

5 Gal

Clean Up:

Protecting Our Environment is important to Nutech Paint:

Clean up with cold water away from drains.

Do not pour leftover paint down the drain.

Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services.

Empty paint containers should be left open in a well-ventilated area to dry out.

Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.

Storage/Shelf Life:

Cool, dry location.
Avoid contact with direct sunlight and heat.

Stored 24 months @ 77 °F

First Aid:

SEEK IMMEDIATE MEDICAL ATTENTION.

Refer to the appropriate **Nutech Safety Data Sheet** (SDS) for further information.
For medical emergencies only, call: 911

- In case of eye contact, flush thoroughly with water for at least 15 minutes
- In case of skin contact, wash affected areas with soap and water
- Remove and wash contaminated clothing
- If inhalation causes physical discomfort, remove it to fresh air

If discomfort persists, or any breathing difficulty occurs or if swallowed, seek medical advice

Warranty:

Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.

Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.

Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages. Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability:

Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.

Disclaimer:

The information given on this data sheet is based on many years' experiences and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information, please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'

The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.



American Distribution

NuTech Paint LLC

19744 Beach Blvd # 369
Huntington Beach CA, 92648
(714) 225-3688
info@nutechpaints.com



NuTech Paints California

714-860-8195

nutechpaintsca@gmail.com

nutechpaintsca.com